Safety Data Sheet

Shell Turbo Oil T 32

Version 1.0	Revision Date 2015/12/31	Print Date 2016/05/02			
1. IDENTIFICATION OF THE HAZARDOUS CHEMICALS AND OF THE SUPPLIER					
Product name	: Shell Turbo Oil T 32				
Product code	: 001A9782				
Manufacturer or supplier's Supplier Telephone Telefax	details Shell Malaysia Trading Sdn Bhd (6087-M) Menara Shell No. 211 Jalan Tun Sambanthan 50470 Kuala Lumpur Malaysia (+60) 3 2385 2888 :				
Emergency telephone number Email Contact for Safety Data Sheet	 1 800 88 3899 If you have any enquiries about the please email lubricantSDS@shell. 				
Recommended use of the of Recommended use	chemical and restrictions on use				
ivecommended use					

2. HAZARDS IDENTIFICATION

GHS Classification

Not a dangerous substance or mixture according to the Globally Harmonised System (GHS).

GHS Label element	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	: Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.

Safety Data Sheet

Shell Turbo Oil T 32

Version 1.0	Revision Date 2015/12/31	Print Date 2016/05/02
	Disposal: No precautionary phrases.	
Sensitising components :	Contains N-phenyl-1-naphthylamine. May produce an allergic reaction.	

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

3. COMPOSITION AND INFORMATION OF THE INGREDIENTS OF THE HAZARDOUS CHEMICAL

Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9.

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration [%]
N-phenyl-1-naphthylamine	90-30-2	Acute Tox.4; H302 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic1; H410 Skin Sens.1; H317	0.1 - 0.24
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 90

For explanation of abbreviations see section 16.

4. FIRST-AID MEASURES

General advice	: Not expected to be a health hazard when used under normal conditions.
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	 Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

rsion 1.0		Revision Date 2015/12/31	Print Date 2016/0
In case of eye contact	:	Flush eye with copious quantities If persistent irritation occurs, obta	
If swallowed	:	In general no treatment is necess are swallowed, however, get med	
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and sympof black pustules and spots on the Ingestion may result in nausea, ve	e skin of exposed areas.
Protection of first-aiders	:	When administering first aid, ensu appropriate personal protective en incident, injury and surroundings.	quipment according to the
Notes to physician	:	Treat symptomatically.	
IRE-FIGHTING MEASURES			
Suitable extinguishing media	:	Foam, water spray or fog. Dry che dioxide, sand or earth may be use	
Unsuitable extinguishing media	:	Do not use water in a jet.	
Specific hazards during firefighting	:	Hazardous combustion products of A complex mixture of airborne sol gases (smoke). Carbon monoxide may be evolved occurs. Unidentified organic and inorganic	lid and liquid particulates d if incomplete combustic
Specific extinguishing methods	:	Use extinguishing measures that circumstances and the surroundir	
Special protective equipment for firefighters	:	Proper protective equipment inclu gloves are to be worn; chemical re- large contact with spilled product Breathing Apparatus must be wor a confined space. Select fire fight relevant Standards (e.g. Europe:	esistant suit is indicated i is expected. Self-Contain m when approaching a fir er's clothing approved to
Hazchem Code	:	NONE/TIADA	
Hazchem Code	: SUF	a confined space. Select fire fight relevant Standards (e.g. Europe: NONE/TIADA	er's clothing approv
Personal precautions, protective equipment and	:	Avoid contact with skin and eyes.	

Version 1.0	Revision Date 2015/12/31 ditches or rivers by using sand, ea barriers.	Print Date 2016/05/02 arth, or other appropriate
	Local authorities should be advise cannot be contained.	d if significant spillages
Methods and materials for containment and cleaning up	: Slippery when spilt. Avoid accident Prevent from spreading by making or other containment material. Reclaim liquid directly or in an abs Soak up residue with an absorbent suitable material and dispose of pr	a barrier with sand, earth sorbent. It such as clay, sand or other
Additional advice	: For guidance on selection of personal see Chapter 8 of this Safety Data For guidance on disposal of spilled this Safety Data Sheet.	Sheet.

	7.	HANDL	ING		STORA	GE
--	----	-------	-----	--	-------	----

Handling		
General Precautions	Use local exhaust ventilation if there is risk of inhalation vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disp this material.	
Advice on safe handling	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear shou worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.	ld be
Avoidance of contact	Strong oxidising agents.	
Product Transfer	This material has the potential to be a static accumulate Proper grounding and bonding procedures should be u during all bulk transfer operations.	
Storage		
Other data	Keep container tightly closed and in a cool, well-ventila place. Use properly labeled and closable containers.	ted
	Store at ambient temperature.	
Packaging material	Suitable material: For containers or container linings, u steel or high density polyethylene. Unsuitable material: PVC.	se mild

Safety Data Sheet

Shell Turbo Oil T 32

Version 1.0	Revision Date 2015/12/31	Print Date 2016/05/02
Container Advice	: Polyethylene containers should not	be exposed to high
	temperatures because of possible r	risk of distortion.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhalable fraction))	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures	 The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
	Adequate ventilation to control airborne concentrations.

Version 1.0	Revision Date 2015/12/31	Print Date 2016/05/02
	Where material is heated, sprayed or a greater potential for airborne concentration	
	General Information: Define procedures for safe handling an controls. Educate and train workers in the haza measures relevant to normal activities product. Ensure appropriate selection, testing a equipment used to control exposure, e equipment, local exhaust ventilation. Drain down system prior to equipment maintenance. Retain drain downs in sealed storage subsequent recycle. Always observe good personal hygien	nd maintenance of rds and control associated with this and maintenance of e.g. personal protective break-in or pending disposal or e measures, such as
	washing hands after handling the mate drinking, and/or smoking. Routinely w protective equipment to remove contai contaminated clothing and footwear th Practice good housekeeping.	erial and before eating, ash work clothing and minants. Discard

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection :	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].
Hand protection Remarks :	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand

Version 1.0		Revision Date 2015/12/31	Print Date 2016/05/02
		care. Gloves must only be worn on clear gloves, hands should be washed and d Application of a non-perfumed moisturing	ried thoroughly.
		For continuous contact we recommend breakthrough time of more than 240 mi for > 480 minutes where suitable gloves short-term/splash protection we recommend recognize that suitable gloves offering to may not be available and in this case a time maybe acceptable so long as appr and replacement regimes are followed. a good predictor of glove resistance to dependent on the exact composition of Glove thickness should be typically gree depending on the glove make and mod	nutes with preference s can be identified. For nend the same, but his level of protection lower breakthrough ropriate maintenance Glove thickness is not a chemical as it is the glove material. ater than 0.35 mm
Eye protection	:	If material is handled such that it could protective eyewear is recommended.	be splashed into eyes,
Skin and body protection	:	Skin protection is not ordinarily required work clothes. It is good practice to wear chemical res	-
Thermal hazards	:	Not applicable	
Environmental exposure cor	ntro	bls	
General advice	:	Take appropriate measures to fulfill the	•

Take appropriate measures to fulling the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.
 Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid at room temperature.
Colour	:	Clear pale yellow
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	<= -22 °C / <= -8 °FMethod: ASTM D97
Initial boiling point and boiling range	:	> 280 °C / 536 °Festimated value(s)
Flash point	:	>= 215 °C / >= 419 °F

sion 1.0	Revision Date 2015/12/31	Print Date 2016/05/02
	Method: ASTM D92	
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Data not available	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: > 1estimated value(s)	
Relative density	: 0.840 (15 °C / 59 °F)	
Density	: 840 kg/m3 (15 °C / 59 °F) Method: ASTM D4052	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: Pow: > 6(based on information o	n similar products)
Auto-ignition temperature	: > 320 °C / 608 °F	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 32 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445	
	5.45 mm2/s (100 °C / 212 °F) Method: ASTM D445	
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to b	pe a static accumulator.
Decomposition temperature	: Data not available	

10. STABILITY AND REACTIVITY

Version 1.0 Reactivity	Revision Date 2015/12/31Print Date 2016/0: The product does not pose any further reactivity hazards addition to those listed in the following sub-paragraph.	
Chemical stability	: Stable.	
Possibility of hazardous reactions	: Reacts with strong oxidising agents.	
Conditions to avoid	: Extremes of temperature and direct sunlight.	
Incompatible materials	: Strong oxidising agents.	
Hazardous decomposition products	: Hazardous decomposition products are not expected to for during normal storage.	orm

11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Symptoms of Overexposure	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		
Product:		
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	:	Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Expected to be of low toxicity:

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating.

Version 1.0

Revision Date 2015/12/31

Print Date 2016/05/02

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a skin sensitiser.

Components:

N-phenyl-1-naphthylamine:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Germ cell mutagenicity

Product:

: Remarks: Not considered a mutagenic hazard.

Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

STOT - single exposure

Product:

Remarks: Not expected to be a hazard.

STOT - repeated exposure

Product:

Remarks: Not expected to be a hazard.

Aspiration toxicity

Product:

10 / 14

Version 1.0

Revision Date 2015/12/31

Print Date 2016/05/02

Not considered an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

12. 1	ECOLOGICAL INFORMATION		
	Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Eco	toxicity		
	Product:		
	Toxicity to fish (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
	Toxicity to crustacean (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
	Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
	Toxicity to fish (Chronic	:	Remarks: Data not available
	toxicity) Toxicity to crustacean	:	Remarks: Data not available
	(Chronic toxicity) Toxicity to microorganisms (Acute toxicity)	:	Remarks: Data not available
	<u>Components:</u> N-phenyl-1-naphthylamine :		
	M-Factor	:	1
Pers	sistence and degradability		
	Product:		

Version 1.0	Revision Date 2015/12/31	Print Date 2016/05/02
Biodegradability	: Remarks: Expected to be not rea constituents are expected to be in contains components that may pe	dily biodegradable., Major nherently biodegradable, but
Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components bioaccumulate.	with the potential to
Partition coefficient: n- octanol/water	: Pow: > 6Remarks: (based on info	ormation on similar products)
Mobility in soil		
Product:		
Mobility	 Remarks: Liquid under most envi enters soil, it will adsorb to soil pa mobile. Remarks: Floats on water. 	
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	 Product is a mixture of non-volati expected to be released to air in Not expected to have ozone depl photochemical ozone creation po potential. Poorly soluble mixture., May caus organisms. Mineral oil is not expected to cau aquatic organisms at concentration 	any significant quantities., letion potential, otential or global warming se physical fouling of aquatic se any chronic effects to

13 DISPOSAL INFORMATION

Disposal methods		
Waste from residues	:	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
		Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.
Contaminated packaging	:	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Version 1.0

Revision Date 2015/12/31

Print Date 2016/05/02

14. TRANSPORTATION INFORMATION

National Regulations

Hazchem Code : NONE/TIADA

International Regulation

ADR

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category Ship type Product name Special precautions	 Not applicable Not applicable Not applicable Not applicable
Special precautions for user	
Remarks	: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Additional Information	: MARPOL Annex 1 rules apply for bulk shipments by sea.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

OSHA 1994 and relevant regulations.

Factories and Machinery Act 1967 and relevant regulations.

Petroleum (Safety Measures) Act 1984.

Environmental Quality Act 1974 and regulation.

Motor Vehicles (Construction and Use) (Vehicles Carrying Petroleum Products) Rules, 1965-L.N.405/65 under Road Transport Act 1987.

Motor Vehicles (Construction, Equipment and Use) (Use Of Liquefied Petroleum Gas Fuel System in Motor Vehicles) Rules 1982 – P.U. (A) 392/82 under Road Transport Act, 1987.

Other international regulations

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.

Version 1.0

Revision Date 2015/12/31

16. OTHER INFORMATION

Full text of H-Stateme	nts	
H302 H304 H317 H373 H400 H410 Full text of other abbr	Harmful if swallowed. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure if swallowed. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. eviations	
Acute Tox. Aquatic Acute Aquatic Chronic Asp. Tox. Skin Sens. STOT RE	Acute toxicity Acute aquatic toxicity Chronic aquatic toxicity Aspiration hazard Skin sensitisation Specific target organ toxicity - repeated exposure	
Abbreviations and Acro	nyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.	
Further information		
Other information	: A vertical bar () in the left margin indicates an amendment from the previous version.	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.